





Metallic Spark Black

RM 43,600

PERFORMANCE

POWER

Engine

4-Stroke, Parallel Twin, DOHC 8 Valve, Liquid Cooled

Wheel Travel

41mm Inverted Telescopic Fork with Adjustable Rebound Damping (right side) and

150 mm

25.0

Fuel Injection Fuel System

649 cc Displacement

Digital

Ignition

Bore X Stroke 83.0 x 60.0 mm

Electric Starter Starting System

Comprehension Ratio 10.8:1

Transmission 6-speed, Return Shift

Max Power 49.0 kW / 8,500 rpm

Wet Multi-disc, Manual Clutch type

61.0 Nm /7,000 rpm Max Torque

Final Drive Sealed Chain

Lubricant System Forced Lub, Semi Dry Sump Front Suspension /

Adjustable Prelaod (Left side),

Caster (Rake angle)

Rear Suspension / Wheel Travel

Offset Laydown Single-shock with Remote Spring Preload

Adjustability, 145 mm

Front Brakes **Dual Semi-floating**

Petal Discs (300mm)

Front Tyre 120/70ZR17M/C (58W)

Rear Brakes Single Disc (250 mm)

Rear Tyre 160/60ZR17M/C (69W)

DETAILS

Frame type	Diamond, High-tensile Steel	Overall length x Width x Height	2,165 x 840 x 1,420 mm
Seat Height	845 mm	Curb Mass	219 kg
Trail	108 mm	Headlight / Brake / Tail Light	LED
Steering angle (Left/Right)	35/35	Wheel Base	1,415 mm
Fuel Capacity	21 L	Ground Clearance	170 mm







Metallic Flat Spark Black / Candy Lime Green

RM 44,200

POWER

PERFORMANCE

Engine Fuel System	4-Stroke, Parallel Twin, DOHC 8 Valve, Liquid Cooled Fuel Injection	Front Suspension / Wheel Travel	41mm Inverted Telescopic Fork with Adjustable Rebound Damping (right side) and Adjustable Prelaod (Left side), 150 mm
Displacement	649 cc	Caster (Rake angle)	25.0
lgnition	Digital	Rear Suspension / Wheel Travel	Offset Laydown Single-shock with Remote Spring Preload Adjustability, 145 mm
Bore X Stroke	83.0 x 60.0 mm		
Starting System	Electric Starter		• • •
Comprehension Ratio	10.8 : 1	Front Ducker	Dual Cami flacting
Transmission	6-speed, Return Shift	Front Brakes	Dual Semi-floating Petal Discs (300mm)
Max Power	49.0 kW / 8,500 rpm	Front Tyre	120/70ZR17M/C (58W)
Clutch type	Wet Multi-disc, Manual	Rear Brakes	Single Disc (250 mm)
Max Torque	61.0 Nm /7,000 rpm	Rear Tyre	160/60ZR17M/C (69W)
Final Drive	Sealed Chain	•	,

Forced Lub, Semi Dry Sump

DETAILS

Lubricant System

Frame type	Diamond, High-tensile Steel	Overall length x Width x Height	2,165 x 840 x 1,420 mm
Seat Height	845 mm	Curb Mass	219 kg
Trail	108 mm	Headlight / Brake / Tail Light	LED
Steering angle (Left/Right)	35/35	Wheel Base	1,415 mm
Fuel Capacity	21 L	Ground Clearance	170 mm